



Trees and equipment maintenance are also hazards. To avoid being struck by trees, restrict worker access during felling, trimming, loading. Use protective structures on equipment. Use safe hoisting, rigging for logs and limbs.

To avoid being struck by equipment parts, do lockout/tagout and hazardous energy control during maintenance, repair, cleaning, and inspection.




©2009 Laborers Health & Safety Fund of North America, Washington, DC
All rights reserved. This material was produced under grant number 46C3-HT06 from the Occupational Safety and Health Administration and is based upon work supported by the Federal Highway Administration under grant agreement DTFH61-06-G-00007. Any opinions, findings, and conclusions or recommendations expressed in this publication are those of the Author(s) and do not necessarily reflect the views or policies of the U.S. Department of Labor or the Federal Highway Administration. No statement made in this booklet should be construed to convey an impression that any member of the consortium, its affiliates, or employees have assumed any part of the employer's exclusive legal responsibility for providing a "safe and healthful workplace" as mandated by the Occupational Safety and Health Act. Nor does mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government. Produced for the consortium by FOF Communications.

Struck or Crushed



How Are Road Workers Struck or Crushed?



Tools and materials are two major hazards. To avoid being struck by tools:

- Use point of operation guarding on portable hand tools.
- Use a chain saw safety program.
- Use Personal Protective Equipment (PPE).

To avoid being struck or crushed by materials:

- Keep out of lifting areas, from beneath loads.



- Use safe methods for rigging, hoisting, and setting steel plates, jersey barriers, manhole frames and covers.
- Use PPE — hard hats, footwear, eye protection.